



The speaker is both visually appealing and produces excellent sound. Users benefit from exceptional sound quality because of the high-class woofer. It is suitable for both indoor and outdoor use due to its excellent temperature resistance and IP66 waterproof rating. With the unique brackets, the speaker may be easily placed at various angles in corners or on solid surfaces such as walls or ceilings. This speaker has a built-in 70V/100V and 8Ω power tap, allowing you to select different power for different occasions. The rated power is 20W, 30W, or 40W. Each speaker has three installation types: Wall-mounted with bracket, can be installed on the wall; Floor-stand with stake, which can be installed in your backyard; You can hang the speaker in your room using the pendant type and a safety rope. This speaker is made from our own mould and is excellent for use in gardens, parks, hotels, and other outdoor settings.

SPECIFICATIONS

Model	CX-DSP4042	CX-DSP4053	CX-DSP4064
Woofer	4" PP Cone	5.25" PP Cone	6.5" PP Cone
Tweeter	0.75" Silk Dome	1" Silk Dome	1" Silk Dome
RMS Power	20W	30W	40W
Frequency Response ($\pm 3\text{dB}$)	120Hz-20kHz	110Hz-20kHz	100Hz-20kHz
Nominal Impedance	8	8	8
Sensitivity	83	84	85
Transformer	8Ω-0-20W-10W-5W-2.5W	8Ω-0-30W-15W-7.5W-3.75W	8Ω-0-40W-20W-10W-5W
IP Level	IP 66	IP 66	IP 66
Product Dimension (mm)	138×190 (5.4"×7.5")	170×240 (6.7"×9.4")	208×280 (8.2"×11")