



The CX-MAG2189 Intelligent Public Address Multimedia Matrix Centre offers a 10.4-inch colour touch screen and automatic Chinese/English display mode conversion for easy use. 1-48 remote paging channels and a robust audio matrix design. Built-in optional module functions include common input, priority input, partition common output, monitoring, and an extended output/input module. Built-in DSPPA sound resource for background music. Support background music without an external source device. It is a Public Address System solution appropriate for medium and large venues such as stations, stadiums, exposition centres, commercial buildings, parks, scenic ports, governments, colleges or universities, hotels, villas, industries, banks, and jails.

SPECIFICATIONS

Model	CX-MAG2189
Display color	Color
Screen size	10.4 inches
Control mode	Touchpad + touch screen
Working environment	Ambient temperature: 5-35°C; relative humidity: ≤75%; air pressure≈86-106kPa
Timing power with load capacity	Single-channel current 2A, 4- channel total current 5A
System audio signal SNR (A-weighted)	≥90dB
System audio signal distortion	0.1% (1kHz)
System audio signal input level range	1Vrms, 2Vrms, 4Vrms optional

System audio signal input impedance	10kΩ
System audio signal nominal output level	0dBV
Self-consumption	AC 220V/50Hz/120W
Package Size (L x W x H)	540*535*355mm
Product Size (L x W x H)	484*408*308mm
Gross weight	35.1kg
Net weight	27kg
Configuration	Manual 1; power cable 1; key 2; protective glass 1
System software	PMM package. All rights reserved. Reproduction or counterfeit is not allowed.