



Integrated one-touch alarm, chime input, Fire Alarm input, eight dry contact inputs, and one dry contact output. The built-in TEL input module, with password control, supports TEL paging to all zones. Support the monitoring function, which may monitor each individual zone separately. Support remote PC control and Android pad control on the same network. Support both AC power input and DC 24V input. Description: The CX-MAG808 digital audio matrix and paging controller is highly integrated, allowing for multi-zone paging and source selection. It includes 8 balanced audio inputs and outputs, as well as remote paging, panel control, computer control, and Android pad control. It provides several audio inputs. It has 8 AUX inputs and supports MP3 playback (built-in or external USB) as well as built-in FM. To better integrate with the emergency system, it offers TEL paging to all zones, a one-touch alarm, 8 dry contact inputs, and 1 dry contact output. It is a comprehensive solution for multi-zone, multi-functional venues such as entertainment centres, large-scale hotels, sports centres, shopping malls, and airports.

SPECIFICATIONS

Model	CX-MAG808
Power supply	-230V/50Hz/DC 24V ~ 230V/50Hz/DC 24V
Input sensitivity of MIC1 & MIC 2	10mV
Input sensitivity of lines 1-8	250mV
Output voltage of lines 1-8	1V
Input sensitivity of EMC	250mV
MIC I/O frequency response (±3dB)	80Hz - 10kHz (±3dB)

Line I/O frequency response (±3dB)	20Hz - 20kHz (±3dB)
Radio frequency band	86-108 MHz
Max. output noise	<3mV
Output distortion (@1kHz)	<1% 1kHz
Machine size	484mm×375mm×132mm (1PS)
Packing size	540mm×510mm×195mm (1PS)
Net weight	10Kg
Gross weight	13Kg (1PS)