



The ConnexAV IC6 in-ceiling speaker is part of the Architect IN line of visibly discrete audio system components. This 2-way midsize speaker is compatible with the majority of high-fidelity amplifiers and home theater receivers on the market today. It supports immersive, multichannel formats and adds a vertical dimension to your Atmos-compatible home theater system. ConnexAV's IN series of in-wall and in-ceiling speakers is suitable for both private and public environments. They are a tribute to ConnexAV's dedication to providing amazing audio quality. The IC6 can be used in a wide range of situations, including conference halls, shopping malls, amphitheatres, restaurants, stores, hotels, offices, private screening rooms, schools, private home theaters, and integrated hi-fi systems. The ConnexAV IC6 in-ceiling speaker has a 2-way coaxial low-mid driver (16.5 cm) made of cellulose fibre and two silk dome tweeters (19 mm) that can be adjusted to send sound waves towards the listening area. The speaker's white, magnetic grille can be painted to match your existing interior design. The IC6 speaker has a sensitivity of 87 dB and a maximum power handling of 100 watts. This type, with a frequency response of 70 Hz to 20 kHz, is an excellent surround speaker choice for a home theater installation.

## SPECIFICATIONS

<b>Type</b>	In-ceiling speaker
<b>Power</b>	70/100V
<b>Loudspeaker</b>	2-way coaxial Mid-bass : 165 mm paper cone, rubber edge Tweeter : 19 mm silk dome, orientation 35° to 40° in all directions
<b>Frequency response (± 3dB)</b>	89Hz-20kHz
<b>Sensitivity</b>	90.3±2dB
<b>Impedance</b>	8 Ohms
<b>Crossover frequency</b>	1950 Hz
<b>Color</b>	White (ready to paint)

<b>Dimensions</b>	190*105mm
<b>Cut-out dimensions</b>	Ø200 mm
<b>Weight</b>	0.9kg
<b>Packaging (unit)</b>	Brown cardboard
<b>Dimensions</b>	W296 x H130 x D279 mm
<b>Weight</b>	2,07 kg
<b>Overbox (8 pcs)</b>	Brown cardboard
<b>Dimensions</b>	Ü
<b>Net / Gross weight</b>	11,6 kg / 18 kg